

BZLI5K_AU

03.05.2021

Illuminated contact block, momentary, T5,5K

General Data

Type reference	BZLI5K_AU
Description	Twin contact block, gold-plated contacts, separate plungers
Approvals	CCC, cCSAus, DNV, ENEC10, VDE, CE, UKCA
Contact type	1 NO
Degree of protection	IP20
Operation travel	3 mm
Connection type	screw connection 2.5 mm ²
Contact material	AgNi, gold-plated
Max. storage temperature	-50°C ... 85°C
Max. operating temperature	-30°C ... 70°C, without illumination -30°C ... 55°C, using incandescent lamps -30°C ... 65°C, using LEDs
Mechanical life	1 million switching cycles
Electrical life (rated load)	1 million switching cycles
Contact resistance NO	< 50 mOhm (new state)
Bouncing time NO	< 10ms

Electrical data acc. to IEC/EN 60947-5-1 (VDE 0660 Sect. 200)

	alternate current	direct current
Utilisation category	-	-
Rated insulation voltage Ui	250 V	-
Rated operating voltage Ue	-	-
Rated operating current Ie	-	-
Breaking capacity	-	-
Continuous thermal current	-	-

Technical Data - Lamp

Lamp socket	T5,5K
Max. lamp voltage	60 V
Max. lamp output	1.2 W



Definition X1 ...anode, X2...cathode

Electrical features - 5µm gold-plating, type addition _AU

Switching voltage 20 mV ... 42 V AC/DC

Switching current 1 mA ... 250 mA

Additional data

Connection range 0.34 ... 2.5 mm²

Tightening torque (screw terminal) 0.4 Nm

