


**BFL5K**

17.12.2010

**Illuminated contact block, maintained, T5,5K**



General Data	
Type reference	BFL5K
Description	Illuminated contact block with screw connections
Approvals	CCC, cCSAus, DNV, ENEC10, VDE, CE, UKCA
Contact type	1 NC + 1 NO
Degree of protection	IP20
Operation travel	3 mm
Connection type	screw connection 2.5 mm <sup>2</sup>
Contact material	AgNi
Max. storage temperature	-50°C ... 85°C
Max. operating temperature	-30°C ... 70°C, without illumination -30°C ... 55°C, using incandescent lamps -30°C ... 65°C, using LEDs
Mechanical life	1 million switching cycles
Electrical life (rated load)	1 million switching cycles
Contact resistance NO	< 20 mOhm (new state)
Contact resistance NC	< 20 mOhm (new state)
Min. current	1 mA (under laboratory conditions)
Min. voltage	5 V
Bouncing time NO	< 10ms
Bouncing time NC	< 10ms

Electrical data acc. to IEC/EN 60947-5-1 (VDE 0660 Sect. 200)		
	alternate current	direct current
Utilisation category	AC15 B300	DC13 Q300
Rated insulation voltage U <sub>i</sub>	250 V	300 V
Rated operating voltage U <sub>e</sub>	240 V	250 V / 125 V / 60 V / 24 V
Rated operating current I <sub>e</sub>	1.5 A	0.2 A / 0.4 A / 1 A / 2 A
Breaking capacity	10I <sub>e</sub>	1,1I <sub>e</sub>
Continuous thermal current	6 A	-



**Electrical data acc. to IEC/EN 61058-1 (VDE 0630 Sect. 1)**

Rated voltage Ue	250 V~
Rated current Ie	6(4) A

**Technical Data - Lamp**

Lamp socket	T5,5K
Max. lamp voltage	60 V
Max. lamp output	1.2 W
Definition	X1...anode, X2...cathode

**Additional data**

Connection range	0.34 ... 2.5 mm <sup>2</sup>
Tightening torque (screw terminal)	0.4 Nm

**Additional electrical data**

Overvoltage category	II
----------------------	----

**Electrical data acc. to IEC/EN 60947-5-1 (VDE 0660 Sect. 200)**

	alternate current	direct current
Utilisation category	DC13	-
Rated insulation voltage Ui	-	-
Rated operating voltage Ue	12 V	-
Rated operating current Ie	6 A	-
Breaking capacity	1,1Ie	-
Continuous thermal current	-	-

**Electrical data acc. to IEC/EN 61058-1 (VDE 0630 Sect. 1)**

Rated voltage Ue	12 V DC
Rated current Ie	6(6) A



