

FRTFO

19.07.2021

Contact block, momentary



General Data

Type reference	FRTFO
Description	Contact block with Faston terminals, separate plungers, latching collar
Approvals	CCC, CE, cURus, ENEC10, VDE, UKCA
Contact type	1 NC
Degree of protection	IP00
Operation travel	2.3 mm
Connection type	Faston terminals 2.8 x 0.8 mm
Contact material	AgNi
Max. storage temperature	-40°C ... 80°C
Max. operating temperature	-25°C ... 70°C
Mechanical life	600,000 switching cycles
Electrical life (rated load)	600,000 switching cycles
Contact resistance NC	< 20 mOhm (new state)
Min. current	1 mA (under laboratory conditions)
Min. voltage	5 V
Bouncing time NC	< 10ms
Positive opening contact	acc. to EN60947-5-1, appendix K

Electrical data acc. to IEC/EN 60947-5-1 (VDE 0660 Sect. 200)

	alternate current	direct current
Utilisation category	AC15 B300	DC13 Q300
Rated insulation voltage Ui	250 V	250 V
Rated operating voltage Ue	240 V / 120 V	250 V / 125 V / 60 V / 24 V
Rated operating current Ie	1.5 A / 3 A	0.27 A / 0.55 A / 1 A / 2 A
Breaking capacity	10Ie	1,1Ie
Continuous thermal current	5 A	-

Electrical data acc. to IEC/EN 61058-1 (VDE 0630 Sect. 1)



Rated voltage U_e 250 V~

Rated current I_e 6(4) A

Note

O = NC contact

DC13: 100.000 switching cycles (at max. switching capacity)
Life time with emergency-stop head: 30.000 (RKUV28, RRJUV)
6.050 (RXJUV)

Data acc. to UL 60947-5-1 / CSA-C22.2 No. 60947-5-1

Rating

Pilot duty B300; 24 V dc/3 A

