

**YPVOOH**

01.06.2021

**Emergency-stop - 2 NC with pull release**

**General Data**

Type reference	YPVOOH
Description	Emergency-stop head, foolproof, pull release
Approvals	CE, cURus, UKCA
Contact type	2 NC
Degree of protection	IP65 / IP67 / IP69K
Connection type	soldering lugs
Contact material	AgNi
Max. storage temperature	-40°C ... 80°C
Max. operating temperature	-25°C ... 70°C
Mechanical life	30,000 switching cycles
Electrical life (rated load)	30,000 switching cycles at rated load
Contact resistance NC	< 20 mOhm
Bouncing time NC	< 10ms
Positive opening contact	acc. to EN60947-5-1, appendix K

**Electrical data acc. to IEC/EN 60947-5-1 (VDE 0660 Sect. 200)**

	alternate current	direct current
Utilisation category	AC15	DC13
Rated insulation voltage $U_i$	250 V	250 V
Rated operating voltage $U_e$	240 V / 35 V	250 V / 35 V
Rated operating current $I_e$	1.5 A / 5 A	0.27 A / 2 A
Breaking capacity	10I <sub>e</sub>	1,1I <sub>e</sub>
Continuous thermal current	5 A	-

**Additional data**

Mounting aperture	16.2 mm
Tightening torque (mounting nut)	0.8 ... 1.5 Nm
Release	pull to release
Mounting position	any



Standards	EN 60947-5-1, EN 60947-5-5, EN ISO 13850
Material group	I
Overvoltage category	II
Pollution degree	2
Operating force	max. 40 N (at 20 mm/min)
Release force	20 N <= Fe <= 50 N
Ld	20% (NC)
B10d [cycles]	179,000

### Note

with switching position indicator  
O = NC contact

Use partially insulated Faston clamps (for versions with Faston connections)!  
Recommended Schlegel type:  
"FHTI2,8x0,5\_01"  
0.5-1.5mm<sup>2</sup> (AWG 20-16)  
-30°C - 75°C

### Data acc. to UL508, IEC60947-5-5

Tightening torque (mounting nut)	0.8 ... 1.5 Nm (plastic nut) 1.2 Nm (metal nut)
Rating contact block	B300/C300 R300, 35 V/ 2A
Enclosure Type	Type 1 (front face)



