

IKSI4

16.07.2018

**with fuseholder, fuse cartridge*)
not included, please order
separately**

***) fuse cartridges acc. to DIN 41571**



General Data

Type Reference:	IKSI4
Description:	Fuse Terminal
Approvals:	CE, CSA
Terminal type:	Fuse terminal, 5x20 mm
Terminal width:	10 mm
Mounting method:	Top hat rail N35, EN60715 TH35
Connection type:	screw connection, slotted screw
Thread size of screw connection:	M3
Torque:	0.8 Nm
Rated cross section:	4 mm ²
Wire size (solid):	0.5 ... 6 mm ²
Wire size (stranded):	0.5 ... 4 mm ²
Rated voltage:	500 V
Rated current:	6.3 A
Max. storage temperature:	-40°C ... 80°C
Max. operating temperature:	-30°C ... 40°C

Data acc. to IEC 60947-7-1

Flammability class acc. to UL94:	V2
Pollution degree :	3
Overvoltage category:	III
Material group:	II
Insulating material:	PA 6.6
Stripping length:	7 mm

Note

Cartridge fuses acc. to DIN 41571
Fuse sizes 5 x 20 mm

Data acc. to CSA C22.2 No 158-10

Torque:	0.8 Nm
---------	--------

Wire size (solid):	24-12 AWG
Rated voltage:	150 V
Rated current:	15 A
Stripping length:	7 mm