

**AZ4I**

07.02.2024

**Contact block, momentary**

**General Data**

Type reference	AZ4I
Description	Twin contact block, separate plungers
Approvals	CCC, CE, ENEC05, KEMA, CE, UKCA, UR
Contact type	4 NO
Degree of protection	IP00
Operation travel	3 / 6 mm
Connection type	Faston terminals 2.8 x 0.8 mm
Contact material	AgNi
Max. storage temperature	-50°C ... 85°C
Max. operating temperature	-30°C ... 70°C
Mechanical life	1 million switching cycles
Electrical life (rated load)	1 million switching cycles at rated load
Contact resistance NO	< 20 mOhm (new state)

**Electrical data acc. to IEC/EN 60947-5-1 (VDE 0660 Sect. 200)**

	alternate current	direct current
Utilisation category	AC15 A300	DC13 Q300
Rated insulation voltage $U_i$	250 V	300 V
Rated operating voltage $U_e$	240 V	250 V / 125 V / 60 V / 24 V
Rated operating current $I_e$	3 A	0.2 A / 0.4 A / 1 A / 2 A
Breaking capacity	10Ie	1,1Ie
Continuous thermal current	6 A	-

**Electrical data acc. to IEC/EN 61058-1 (VDE 0630 Sect. 1)**

Rated voltage $U_e$	250 V~
Rated current $I_e$	6(4) A

**Additional data**


Overvoltage category	II
Pollution degree	2

**Note**

also suitable for actuators with a travel of 3 mm



3mm	0	1	2	3			
6mm	0	1	2	3	4	5	6
23/24	[Progressive switch diagram]						
13/14	[Progressive switch diagram]						
43/44	[Progressive switch diagram]						
33/34	[Progressive switch diagram]						

