

FRPVKOO

26.03.2019

Emergency-stop



General Data

Type reference	FRPVKOO
Description	Emergency-stop head, foolproof, pull release
Approvals	CCC, CE, cURus, TÜV_Süd, UKCA
Contact type	2 NC
Degree of protection	IP65 / IP67
Connection type	Faston terminals 2.8 x 0.8 mm
Contact material	AgNi
Max. storage temperature	-40°C ... 80°C
Max. operating temperature	-25°C ... 70°C
Mechanical life	30,000 switching cycles
Electrical life (rated load)	30,000 switching cycles at rated load
Contact resistance NC	< 50 mOhm (new state)
Bouncing time NC	< 10ms
Positive opening contact	acc. to EN60947-5-1, appendix K

Electrical data acc. to IEC/EN 60947-5-1 (VDE 0660 Sect. 200)

	alternate current	direct current
Utilisation category	AC15 B300	DC13 Q300
Rated insulation voltage Ui	250 V	250 V
Rated operating voltage Ue	240 V / 120 V	250 V / 125 V / 60 V / 24 V
Rated operating current Ie	1.5 A / 3 A	0.27 A / 0.55 A / 1 A / 2 A
Breaking capacity	10Ie	1,1Ie
Continuous thermal current	5 A	-

Additional data

Mounting aperture	22.3 mm
Tightening torque (mounting nut)	1.3 ... 1.9 Nm
Release	pull to release
Mounting position	any



Standards EN 60947-5-1, EN 60947-5-5, EN ISO 13850

Release force ≤ 30 N (new state)

Ld 20% (NC)

B10d [cycles] 170,000

Pollution degree 3

Note

- with switching position indicator
- O = NC contact
- use partially or fully insulated Faston clamps.

Data acc. to UL

Rating contact block Silver: B300, 24 V DC/3 A
Gold: 42 V DC/100 mA

Lamp rating LED: 30 V AC/DC (4 mA at 24 V)

NEMA TYPE 4x indoor (front face)

