

BZLII

28.06.2021

Illuminated contact block, momentary, W2x4,6d

General Data

Type reference	BZLII
Description	Illuminated twin contact block, separate plungers
Approvals	CCC, cCSAus, DNV, ENEC10, VDE, CE, UKCA, UR
Contact type	2 NO
Degree of protection	IP00
Operation travel	3 mm
Connection type	Faston terminals 2.8 x 0.8 mm
Contact material	AgNi
Max. storage temperature	-50°C ... 85°C
Max. operating temperature	-30°C ... 70°C, without illumination -30°C ... 55°C, using incandescent lamps -30°C ... 65°C, using LEDs
Mechanical life	1 million switching cycles
Electrical life (rated load)	1 million switching cycles at rated load
Contact resistance NO	< 20 mOhm (new state)
Min. current	1 mA
Min. voltage	5 V
Bouncing time NO	< 10ms

Electrical data acc. to IEC/EN 60947-5-1 (VDE 0660 Sect. 200)

	alternate current	direct current
Utilisation category	AC15 B300	DC13 Q300
Rated insulation voltage U_i	250 V	300 V
Rated operating voltage U_e	240 V	250 V / 125 V / 60 V / 24 V
Rated operating current I_e	1.5 A	0.2 A / 0.4 A / 1 A / 2 A
Breaking capacity	10Ie	1,1Ie
Continuous thermal current	6 A	-

Electrical data acc. to IEC/EN 61058-1 (VDE 0630 Sect. 1)

Rated voltage U_e	250 V~
---------------------	--------



Rated current I_e	6(4) A
---------------------	--------

Technical Data - Lamp

Lamp socket	W2x4,6d
-------------	---------

Max. lamp voltage	60 V
-------------------	------

Max. lamp output	1.2 W
------------------	-------

Definition	X1...anode, X2...cathode
------------	--------------------------

Electrical data acc. to IEC/EN 60947-5-1 (VDE 0660 Sect. 200)

	alternate current	direct current
Utilisation category	DC13	-
Rated insulation voltage U_i	-	-
Rated operating voltage U_e	12 V	-
Rated operating current I_e	6 A	-
Breaking capacity	1,1I _e	-
Continuous thermal current	-	-

Electrical data acc. to IEC/EN 61058-1 (VDE 0630 Sect. 1)

Rated voltage U_e	12 V DC
---------------------	---------

Rated current I_e	6(6) A
---------------------	--------

Data cc. to UL508/ CSA 22.2 No. 14-18

Rating	B300, Q300 pilot duty
--------	-----------------------

Lamp rating	1.2 W, 60 V max
-------------	-----------------



