

SVACFT_ALLE**General Data**

Type reference:	SVACFT(L)(X)(F)(P)
Description:	Single Membrane Pushbutton with integrated contact block, with Faston or PCB-mount terminals
Approvals:	CE, DGUV_Test, ENEC10, VDE, CE
Nature of contact:	1 inverter
Degree of protection:	IP66 / IP67 / IP69K
Operation travel:	1.8 mm
Connection type:	Faston terminals 2.8x0.8 mm / PCB-mount terminals
Max. storage temperature:	-40°C ... 80°C
Max. operating temperature:	-25°C ... 70°C
Mechanical life:	1 million switching cycles (20°C)
Contact resistance NO:	< 50 mOhm (new state)
Contact resistance NC:	< 100 mOhm (new state)
Bouncing time NO:	< 10 ms
Bouncing time NC:	< 10 ms

Technical Data - Lamp

Lamp socket:	with integrated white 3 mm LED
Max. lamp voltage:	30 V AC/DC
Max. lamp output:	14mA (at 24 V DC)
Definition:	X1...anode, X2...cathode

Additional Data

Mounting aperture:	22.3mm
Tightening torque (mounting nut):	1.5 ... 1.9 Nm
Mounting position:	any
Standards:	EN 61058-1







Electrical Features

Rated voltage:	20mV ... 48V AC/DC
Rated current:	0.01mA ... 100mA

Note

SVACFT(L)(X)(F)(P)(Z) ()...optional
(L) = illuminating option
(X) = foil ring colours: standard=black (W=white, R=red, Y=yellow,G=green, B=blue)
(F) = with Faston terminals 2.8x0.8mm
(P) = with PCB-mount terminals
(Z) = base-plate mounted version with PCB-mount terminals

- subject to alterations -



- subject to alterations -