


IK3BL

21.04.2021


General Data

Type Reference	IK3BL
Description	Feed-through terminal, screw connection
Approvals	CE, CSA, Lloyds, UKCA, UR
Terminal type	Terminal block
Terminal width	5.1 mm
Mounting method	top hat rail N35, EN60715 TH35
Connection type	screw connection, slotted screw
Thread size of screw connection	M2.5
Torque	0.5 Nm
Rated cross section	2.5 mm ²
Wire size (solid)	0.5 ... 4 mm ²
Wire size (stranded)	0.5 ... 2.5 mm ²
Rated voltage	750 V
Rated current	25 A
Max. storage temperature	-40°C ... 80°C
Max. operating temperature	-30°C ... 40°C

Photo

Data acc. to IEC 60947-7-1

Flammability class acc. to UL94	V2
Pollution degree	3
Overvoltage category	III
Material group	II
Insulating material	PA 6.6
Stripping length	8 mm

Data acc. to UL1059

Torque	5 lb In
Wire size (solid)	22-12 AWG



Rated voltage 600 V

Rated current 20 A

Data acc. to UL1059

Wire size (solid) 12 AWG

Rated voltage 600 V

Rated current 25 A

Data acc. to UL1059

Torque 0.5 Nm

Wire size (solid) 18-12 AWG

Rated voltage 600 V

Rated current 25 A

Data acc. to UL1059

Wire size (solid) 18-12 AWG

Rated voltage 600 V

Rated current 25 A

