

QRBLUVSE

07.07.2021

Illuminated emergency-stop head



General Data

Type reference	QRBLUVSE
Description	Illuminated emergency-stop head with lock, foolproof
Approvals	CCC, cULus, TÜV_Süd, UKCA, UR
Degree of protection	IP65
Max. storage temperature	-50°C ... 85°C
Max. operating temperature	-30°C ... 55°C
Mechanical life	50,000 switching cycles

Technical data

Mounting aperture	22.3 mm
Tightening torque (mounting nut)	max. 2.5 Nm
Release	key release
Illumination	24 V / 15 mA AC/DC
Mounting position	any
Standards	EN 60947-5-1, EN 60947-5-5, EN ISO 13850

Note

- with switching position indicator
- yellow anti-lock collar
- with LED ring illumination
- foolproof acc. to EN ISO 13850

Remark

Anschluss durch Anschlussmodul MAL mit Schraubanschlüssen 2x2,5mm² fingersicher nach VBG4; 2-adrige Litze 0.25mm², ca. 10cm lang mit angecrimptem BKL-Steckverbinder

Data acc. to UL 60947-5-1 / CSA-C22.2 No. 60947-5-1

NEMA TYPE	1 indoor
-----------	----------

Data acc. to UL508



NEMA TYPE

Type 1 (front face)

