

FK16

12.02.2018


General Data

Type Reference	FK16
Description	Railless terminal block
Approvals	CE, CSA, UKCA, UR
Terminal type	Terminal block for railless mounting
Terminal width	10 mm
Mounting method	screw fastening
Connection type	screw connection, slotted screw
Thread size of screw connection	M4
Torque	1.2 Nm
Rated cross section	16 mm ²
Wire size (solid)	0.5 ... 16 mm ²
Wire size (stranded)	0.5 ... 16 mm ²
Rated voltage	750 V
Rated current	76 A
Max. storage temperature	-40°C ... 80°C
Max. operating temperature	-30°C ... 40°C

Photo

Data acc. to IEC 60947-7-1

Flammability class acc. to UL94	V2
Pollution degree	3
Overvoltage category	III
Material group	II
Insulating material	PA 6.6
Stripping length	11 mm

Data acc. to CSA C22.2 No 14

Wire size (solid)	6 AWG
Rated voltage	600 V



Rated current 80 A

Data acc. to CSA C22.2 No 14

Torque 18 Lb In

Wire size (solid) 22-6 AWG

Rated voltage 600 V

Rated current 65 A

Data acc. to CSA C22.2 No 14

Torque 1.2 Nm

Wire size (solid) 20-6 AWG

Rated voltage 600 V

Rated current 68 A

