

FRTFLOI

19.07.2021

Illuminated contact block, momentary



General Data	
Type reference	FRTFLOI
Description	Illuminated contact block with Faston terminals, separate plungers, latching collar
Approvals	CCC, CE, cURus, ENEC10, VDE, TÜV_Süd, UKCA
Contact type	1 NC + 1 NO
Degree of protection	IP00
Operation travel	2.3 mm
Connection type	Faston terminals 2.8 x 0.8 mm
Contact material	AgNi
Max. storage temperature	-40°C ... 80°C
Max. operating temperature	-25°C ... 70°C
Mechanical life	600,000 switching cycles
Electrical life (rated load)	600,000 switching cycles
Contact resistance NO	< 20 mOhm (new state)
Contact resistance NC	< 20 mOhm (new state)
Min. current	1 mA (under laboratory conditions)
Min. voltage	5 V
Bouncing time NO	< 10ms
Bouncing time NC	< 10ms
Positive opening contact	acc. to EN60947-5-1, appendix K

Electrical data acc. to IEC/EN 60947-5-1 (VDE 0660 Sect. 200)		
	alternate current	direct current
Utilisation category	AC15 B300	DC13 Q300
Rated insulation voltage Ui	250 V	250 V
Rated operating voltage Ue	240 V / 120 V	250 V / 125 V / 60 V / 24 V
Rated operating current Ie	1.5 A / 3 A	0.27 A / 0.55 A / 1 A / 2 A
Breaking capacity	10Ie	1,1Ie
Continuous thermal current	5 A	-

Electrical data acc. to IEC/EN 61058-1 (VDE 0630 Sect. 1)



Rated voltage Ue	250 V~
Rated current Ie	6(4) A

Technical Data - Lamp

Lamp socket	none, with integrated LED
Max. lamp voltage	30 V AC/DC
Definition	X1...anode, X2...cathode

Additional data

Overvoltage category	II
Pollution degree	2

Note

I = NO contact; O = NC contact

DC13: 100.000 switching cycles (at max. switching capacity)

Data acc. to UL 60947-5-1 / CSA-C22.2 No. 60947-5-1

Rating	Pilot duty B300; 24 V dc/3 A
--------	------------------------------



