

**SDVA22RRP**

08.09.2023

**Protection cap for hygienic applications**

**General Data**

Type reference	SDVA22RRP
Degree of protection	IP66 / IP69K
Max. storage temperature	-40°C ... 85°C
Max. operating temperature	-40°C ... 85°C
Material	stainless steel 1.4404
Tightening torque (mounting nut)	see *1)
Panel thickness	see *1)
Mounting aperture	22.3 mm

**Note**

P = hygienic protection  
 - captive lid, threadable, also for use with key actuators  
 - twist-proof  
 - suitable for the ranges Rontron-R-Juwel, Rondex-Juwel and Shortron  
 - resistant to cleaning and disinfection agents  
 - FDA conform gasket

Norm: DIN EN 1672-2 2021-5  
 Planned approvals: DGUV

Attention: Observe the overall height of the components used.

1\*) tightening torques / mounting plate thicknesses:

Rontron-R-Juwel (RRJ...):

Panel thickness: 2.0...4.5 mm  
 Fixing nut: R16X1\_423 (M24.287.4B)  
 Tightening torque: 0.8 ... 1.5 Nm

Rondex-Juwel (JR...):

Panel thickness: 0.5...2.0 mm  
 Fixing nut: standard nut JR (M15.139.4E)  
 Tightening torque: 1.5...2.2 Nm

Panel thickness: 1.5...8.0 mm  
 Fixing nut: FRVKM22 (M15.277.4BA)  
 Tightening torque: 0.8...1.5 Nm

Shortron (ST...):

Panel thickness: 0.5...4.0 mm  
 Fixing nut: standard nut (M15.233.4A)  
 Tightening torque: 1.0...2.0 Nm

Panel thickness: 1.5...6.5 mm  
 Fixing nut: FRVKM22 (M15.277.4BA)  
 Tightening torque: 0.8...1.3 Nm



