

**PTSLOI**

28.03.2022

**Illuminated contact block, momentary**

**General Data**

Type reference	PTSLOI
Description	Contact block for base-plate mounting, with positive opening contact
Approvals	CCC, CE, cURus, ENEC10, VDE, TÜV_Süd, UKCA
Contact type	1 NC + 1 NO
Degree of protection	IP00
Operation travel	2.3 mm
Connection type	PCB-mount terminals
Contact material	AgNi
Max. storage temperature	-40°C ... 80°C
Max. operating temperature	-25°C ... 70°C
Mechanical life	1 million switching cycles
Electrical life (rated load)	1 million switching cycles at rated load AC
Contact resistance NO	< 20 mOhm (new state)
Contact resistance NC	< 20 mOhm (new state)
Min. current	1 mA (under laboratory conditions)
Min. voltage	5 V
Bouncing time NO	< 10ms
Bouncing time NC	< 10ms
Positive opening contact	acc. to EN60947-5-1, appendix K

**Electrical data acc. to IEC/EN 60947-5-1 (VDE 0660 Sect. 200)**

	alternate current	direct current
Utilisation category	AC15 B300	DC13 Q300
Rated insulation voltage $U_i$	250 V	250 V
Rated operating voltage $U_e$	240 V / 120 V	250 V / 125 V / 60 V / 24 V
Rated operating current $I_e$	1.5 A / 3 A	0.27 A / 0.55 A / 1 A / 2 A
Breaking capacity	10I <sub>e</sub>	1,1I <sub>e</sub>
Continuous thermal current	5 A	-

**Electrical data acc. to IEC/EN 61058-1 (VDE 0630 Sect. 1)**


Rated voltage U <sub>e</sub>	250 V~
Rated current I <sub>e</sub>	6(4) A

### Technical Data - Lamp

Lamp socket	none, with integrated LED
Max. lamp voltage	30 V AC/DC
Max. lamp output	14 mA (at 24 V DC)
Definition	X1...anode, X2...cathode

### Additional data

Pollution degree	2
Overvoltage category	II
Rated impulse voltage	2.5 kV
Soldering method	wave and manual soldering

### Note

O = NC contact; I = NO contact

The contact unit is being snapped into neck of the pushbutton/switch head.  
Spacer sleeves ensure the correct distance of the connection between PCB and mounting plate.  
The fixing nut must be secured against loosening.

DC13 life time: 100.000 at max. load, 10 operations/minute

Installation instruction:  
The position offset between the operator element and the switching element must be in a  $\varnothing$  0.2 mm circle.

### Data acc. to UL508




Rating	Pilot duty B300; 24 V dc/3 A
--------	------------------------------





11/12  
23/24

0 1 2



Sicht auf Bestückungsseite  
der Leiterplatte

