

## YV\_ALLE

11.02.2021

### General Data

Type reference:	YV(O)(OO)(H)(OOI)(LOO)(LO)(_AU)(_R0)(_674)
Description:	Emergency-stop head, foolproof
Approvals:	CE, cURus, TÜV_Süd
Contact type:	2NC / 2NC+1NO / 1NC
Degree of protection:	IP65 / IP67 / IP69K
Connection type:	Faston terminals 2.8 mm x 0.5 mm / soldering lug
Contact material:	AgNi / AgNi, gold-plated 5µm (_AU)
Max. storage temperature:	-40°C ... 80°C
Max. operating temperature:	-25°C ... 70°C
Mechanical life:	50.000
Electrical life (rated load):	50,000 switching cycles at rated load
Contact resistance NO:	< 20 mOhm/< 50 mOhm (Au)
Contact resistance NC:	< 20 mOhm/< 50 mOhm (Au)
Bouncing time NO:	
Bouncing time NC:	< 10ms
Positive opening contact:	acc. to EN60947-5-1, appendix K

### Electrical data acc. to IEC/EN 60947-5-1 (VDE 0660 Sect. 200)

	alternate current	direct current
Utilisation category	AC15	DC13
Rated insulation voltage Ui	250 V	250 V
Rated operating voltage Ue	35 V	35 V
Rated operating current Ie	5 A	2 A
Breaking capacity	10Ie	1,1Ie
Continuous thermal current	5 A	

### Technical Data - Lamp

Lamp socket:	none, with integrated LED
Max. lamp voltage:	30 V AC/DC
Max. lamp output:	8mA/4.5 mA (at 24 V DC/AC)
Definition:	X1...anode, X2...cathode

### Additional data

Mounting aperture:	16.2 mm
Tightening torque (mounting nut):	0.8 ... 1.5 Nm
Release:	twist release, left or right
Mounting position:	any
Standards:	EN 60947-5-1, EN 60947-5-5, EN ISO 13850
Material group:	I
Overvoltage category:	II
Pollution degree :	2

### Electrical features - 5µm gold-plating, type addition ...AU

Operational voltage:	20 mV...35 V AC/DC
Operational current AC/DC:	1mA ... 100mA
Operating force:	approx. 25 N (at 20 mm/min)
:	
Ld:	20% (NC)
B10d:	250.000

### Note

- with switching position indicator
- O= NC contact, I = NO contact, L = lamp
- H = version with soldering lug for manual soldering (YVOH..., YVOOH...)
- \_674 ...with aluminum fixing nut for panel thickness: 1.5...3.0 mm  
tightening torque fixing nut: 1.2 Nm
- \_R0 ...0 ohm series resistor, with protective diode (series-connected)  
LED cut-off voltage: max. 75 V (with protective diode)  
If LED, max: 25 mA  
Uf LED, typical: 3.2 V (20mA)

- Use partially insulated Faston clamps (for versions with Faston connections)!

Recommended Schlegel type: "FHTI2,8x0,5\_01"  
0.5-1.5mm<sup>2</sup> (AWG 20-16)  
-30°C - 75°C

Additional data for versions without assignment of 3rd contact/illumination (type YVOO):

acc. to IEC/EN 60947-5-1 (VDE 0660 Part 200)

AC15 B300: Ue/Ie 240V 1.5A

DC13 Q300: Ue/Ie 250V 0.27A

Note for version "H" (soldering lug):

When soldering the strands to the soldering lugs make sure that during the soldering process the necessary air and creepage distances between soldering lug and fixing nut are not reduced (possibly caused by solder splashes or protruding strands).

Note for version "\_R0" (0 ohm series resistor):

The LED must not be operated without series resistor.  
Do not connect terminals X1-X2 directly to voltage. Observe LED data!

Data acc. to UL508, IEC60947-5-5

Tightening torque (mounting nut):	0.8 ... 1.5 Nm (plastic nut) 1,2 Nm (metal nut)
Rating contact block:	Silver: 35V AC/DC, 2A; Gold: 35VDC/100mA
Lamp rating:	30 V AC/DC; Rated power max.: 8mA/4.5mA (at 24 V DC/AC)

