

DL

28.08.2008

Lamp module



General Data

Type reference	DL
Description	Lampholder BA9s
Approvals	CCC, cCSAus, DNVGL, KEMA KEUR, UKCA, VDE, CE
Contact type	lampholder
Degree of protection	IP20
Connection type	Cage-Clamp 0.08-2.5 mm ²
Max. storage temperature	-40°C ... 70°C
Max. operating temperature	-25°C ... 55°C

Electrical data acc. to IEC/EN 60947-5-1 (VDE 0660 Sect. 200)

	alternate current	direct current
Utilisation category	-	-
Rated insulation voltage U _i	600 V	-
Rated operating voltage U _e	-	-
Rated operating current I _e	-	-
Breaking capacity	-	-
Continuous thermal current	-	-

Technical Data - Lamp

Lamp socket	BA9s
Max. lamp voltage	250 V
Max. lamp output	2 W
Definition	X1...anode, X2...cathode

Additional data

Enclosure material	PA 6.6
--------------------	--------

Environmental / climatic tests



Vibration resistance	50m/s ² at 5-150Hz according to DIN IEC 68 2-6
Shock resistance	30m/s ² at 50ms acc. to DIN IEC 68 2-27
Constant climatic resistance	IEC 600-68-2-3 and 2-30

