

**FRTFO\_AU**

16.07.2021

**Contact block, momentary**



**General Data**

Type reference	FRTFO_AU
Description	Contact block with Faston terminals, separate plungers, latching collar, gold-plated contacts
Approvals	CCC, CE, cURus, ENEC10, VDE, UKCA
Contact type	1 NC
Degree of protection	IP00
Operation travel	2.3 mm
Connection type	Faston terminals 2.8 x 0.8 mm
Contact material	AgNi, gold-plated
Max. storage temperature	-40°C ... 80°C
Max. operating temperature	-25°C ... 70°C
Mechanical life	600,000 switching cycles
Electrical life (rated load)	600,000 switching cycles
Contact resistance NC	< 50 mOhm (new state)
Min. current	1 mA (under laboratory conditions)
Min. voltage	5 V
Bouncing time NC	< 10ms
Positive opening contact	acc. to EN60947-5-1, appendix K

**Electrical data acc. to IEC/EN 60947-5-1 (VDE 0660 Sect. 200)**

	alternate current	direct current
Utilisation category	AC15	DC13
Rated insulation voltage Ui	250 V	250 V
Rated operating voltage Ue	-	-
Rated operating current Ie	-	-
Breaking capacity	-	-
Continuous thermal current	-	-

**Electrical features - 5µm gold-plating, type addition \_AU**



Switching voltage 20 mV ... 42 V AC/DC

Switching current 1 mA ... 250 mA

**Note**

O = NC contact

DC13: 100.000 switching cycles (at max. switching capacity)  
Life time with emergency-stop head: 30.000 (RKUV28, RRJUV)  
6.050 (RXJUV)

**Data acc. to UL 60947-5-1 / CSA-C22.2 No. 60947-5-1**

Rating 42 V dc/100 mA

